



STANDART TİP GMK Y/D SERİSİ KONDENSERLER / Standart Type GMK Y/D Series Condensers

GMK Y/D - Ø800 mm (880dd / 660dd)	KAPASİTE Capacity		HAVA DEBİSİ Air Cap.		İSİ TRANSFER YÜZEYİ Heat Transfer Surface	BORU HACMI Tube Volume	FAN SAYISI Quantity of Fan	FAN MOTORU Fan Motor				SES SEVİYESİ Sound Level		BOYUTLAR / Dimensions						BAĞLANTILAR Connections	
	3/400V , 50 Hz		3/400V , 50 Hz					GÜÇ / AKIM Power/Current				3/400V , 50 Hz								Giriş (Ø) Inlet	Çıkış (Ø) Outlet
	Δ	y	Δ	y				Δ	y	Δ	y	Δ	y	A	B	D	H	G	E		
	880 d/d	660 d/d	880 d/d	660 d/d				880 d/d	660 d/d	880 d/d	660 d/d	880 d/d	660 d/d	mm	mm	mm	mm	mm	mm	mm	mm
kw		m³/h		m²	dm³	adet	kw	A	kw	A	dB(A)										
GMK Y/D 80.1.1-1325	57,8	47,1	18600	14000	110,6	21,5	1x1	2.0	4.0	1.25	2.3	52	45	1280	1450	1250	1450	700	1270	35	28
GMK Y/D 80.1.1-1321	61,2	49,1	18100	13500	130,3																
GMK Y/D 80.2.1-1325	117,0	95,5	37200	28000	221,2	43,1	1x2	4.0	8.0	2.5	4.6	55	48	2480	2650	1250	1450	700	1270	35	28
GMK Y/D 80.2.1-1321	123,5	99,4	36200	27000	260,6																
GMK Y/D 80.3.1-1325	173,8	141,4	55800	42000	331,8	64,6	1x3	6.0	12.0	3.75	6.9	57	50	3680	3850	1250	1450	700	1270	42	35
GMK Y/D 80.3.1-1321	184,0	147,5	54300	40500	390,9																
GMK Y/D 80.4.1-1325	234,4	191,3	74400	56000	442,4	86,2	1x4	8.0	16.0	5.0	9.2	58	51	4880	5050	1250	1450	700	1270	54	42
GMK Y/D 80.4.1-1321	247,5	199,1	72400	54000	521,2																
GMK Y/D 80.4.2-1325	234,2	191,1	74400	56000	442,4	86,2	2x2	8.0	16.0	5.0	9.2	58	51	2480	2650	2400	1450	700	1270	42x2	35x2
GMK Y/D 80.4.2-1321	247,2	199,0	72400	54000	521,2																
GMK Y/D 80.6.2-1325	347,6	282,9	111600	84000	663,6	129,3	2x3	12.0	24.0	7.5	13.8	60	53	3680	3850	2400	1450	700	1270	54x2	42x2
GMK Y/D 80.6.2-1321	368,0	295,0	108600	81000	781,7																
GMK Y/D 80.8.2-1325	468,8	382,6	148800	112000	884,8	172,4	2x4	16.0	32.0	10.0	18.4	61	54	4880	5050	2400	1450	700	1270	54x2	42x2
GMK Y/D 80.8.2-1321	495,0	398,1	144800	108000	1042,3																
GMK Y/D 80.10.2-1325	570,3	464,0	186000	140000	1106,0	215,5	2x5	20.0	40.0	12.5	23.0	62	55	6080	6250	2400	1450	700	1270	66x2	54x2
GMK Y/D 80.10.2-1321	604,5	484,4	181000	135000	1303,0																